P1000T Slotted Unistrut Channel – 10 ft. lengths





P1000 Standard Channel – 10 ft. lengths





Steel Pipe and Tube Clamps

For use with P1000T & P1000 channels

	Pipe Clamps		Tube Clamps	
A	Part No.	Pipe Size	Part No.	Tube Size O.D.
200	P1109	3/8"	P2024	1/4"
	P1111	1/2"	P2025	3/8"
	P1112	3/4"	P2026	1/2"
	P1113	1"	P2027	5/8"
	P1114	1 1/4"	P2028	3/4"
A	P1115	1 1/2"	P2029	1"
	P1117	2"	P2030	1 1/4"
Steel Clamps			P2032	1 1/2"
			P2034	2"

Lubrication Systems & Devices

PRO/MARK INDUSTRIALS

Div. R.D. Lewis Sales Limited

P.O. Box 26028, Cambridge, Ont. N1R 8E8 Phone (519) 621-0479 (800) 263-9865 Fax. (519) 621-1972 E-mail: sales@promarkindstrials.com

9.5

23.3

1 18.0

Cushion Clamps Steel Pipe and Tube Clamps

For use with P1000T & P1000 channels

	Cushion Pipe Clamps		s Cushior	Cushion Tube Clamps	
~	Part No.	Pipe Size	Part No.	Tube Size O.D.	
IO	009N012	1/4"	004T008	1/4"	
	011N014	3/8"	006T010	3/8"	
	014N018	1/2"	008T012	1/2"	
	017N022	3/4"	010T014	5/8"	
-45	021N026	1"	012T016	3/4"	
	027N032	1 1/4"	016T020	1"	
	030N034	1 1/2"	020T024	1 1/4"	
Cushion Clamps	038N044	2"	024N028	1 1/2"	
Cushion Clamps are used in areas where			032N036	2"	

Featuring the Unique Unistrut Connection

Cushion Clamps are used in areas where there is allot of vibration. The cushion can also serve as an insulator for copper pipes & tubes to prevent electrolysis.

> P1008 3/8"-16 Channel Nut



No Welding

- No Drilling
- 100% Adjustable
- 100% Reusable

The original strut system, Unistrut Metal Framing is the time and moneysaving alternative to conventional support methods. The Unistrut system eliminates welding and drilling, and is easily adjustable, demountable and reusable.



STEP 1 - Insert the spring nut anywhere along the continuous slotted channel. Rounded nut ends permit easy insertion.

STEP 2 - A 90° clockwise turn aligns the grooves in the nut with the inturned edges of the channel. Fittings can be placed anywhere along the channel opening.



STEP 3 - Insert bolt through fitting and into the spring nut.

- STEP 4 Additional channel sections can now be bolted to the fitting already in place by using steps 1-3.
- STEP 5 Tightening with a wrench locks the serrated teeth of the nut into the inturned edges of the channel, forming a strong, vise-like connection.









Div. R.D. Lewis Sales Limited

Lubrication Systems & Devices

P.O. Box 26028, Cambridge, Ont. N1R 8E8 Phone (519) 621-0479 (800) 263-9865 Fax. (519) 621-1972 E-mail: sales@promarkindstrials.com