## **Manual High Pressure Grease Pumps**



#### Portable High Pressure Manual Grease Pumps

For applications where the grease has to be transported or carried to the point of use. Three thumb screws secure the unit to standard 20 liter pails. Follower plate ensures a positive prime to the pump. Maximum operating pressure – 5,000 to 5,800 psi Grease dispense hose – $\frac{1}{4}$ " x 8 ft. Rigid extension with 4 jaw grease fitting coupler

**Part No. 60280-55** Pail cover - 11" diameter Follower plate – 10" diameter

Part No. 60310-55 Pail cover – 12" diameter Follower plate – 12" diameterrt

#### Part No. 68012-55 Portable Manual Grease Pump

For applications where the grease has to be transported or carried to the point of use. Self contained pump and reservoir package with convenient carrying handle keeps the grease container secured and the grease clean. Spring loaded follower plate ensures a positive prime to the pump. Unit is filled by transfer of the grease from standard drums or containers into the reservoir of the 68012-55.

Maximum operating pressure -5,000 to 5,800 psi Grease reservoir capacity -29 lbs. Grease dispense hose  $-\frac{1}{4}$ " x 8 ft.

Rigid extension with 4 jaw grease fitting coupler





# Manual Grease Pumps

## **Manual Grease Gun Filler Pumps**



#### **Manual Grease Filler Pumps**

Comes with filler socket for filling grease guns. Container cover Follower plate Delivery: up to 1 oz. per stroke

#### Part No. 327 for 55 KG Kegs

#### Part No. 328 for 17 KG Pails

#### NOTE:

Comes with a filler socket to connect to filler nipple on ALT grease guns For Alemite grease guns order AL-306741 filler socket

For Lincoln grease guns order LI-80133 filler socket

### Filler Pumps for Automated Grease Systems

Manual filler pumps for filling reservoirs on automated grease systems

Note: coupler to reservoir not included



#### Model Number 327-120HA

Specifications. Container Size: For use on 55 KG kegs Delivery: Variable stroke, up to 1 oz. per stroke. Follower Plate: Included Keg Cover: Included Dispense Hose: 10 ft. (Note: coupler to reservoir not included) Head Construction: Die cast aluminum. Pump Tube: Zinc Plated

### Model Number 328-120HA Specifications. Container Size: For use on 17 KG pails Delivery: Variable stroke, up to 1 oz. per stroke.

Follower Plate: Included Keg Cover: Included Dispense Hose: 10 ft. (Note: Coupler to reservoir not included Head Construction: Die cast aluminum. Pump Tube: Zinc Plated